

VERSION: 02

ISSUED: FEB 2025

LARSEN

TILING

TECHNICAL DATA SHEET

Water Resistant Wood Glue

WATER RESISTANT

WOODEN & LAMINATE FLOORING

GENERAL PURPOSE WOODWORKING

EN 204 CATEGORY D3/3 AND D3/4

Water Resistant Wood Glue is a one-pack, ready to use, general purpose, water-resistant adhesive for wood. Water Resistant Wood Glue offers a fast rate of strength development. Water Resistant Wood Glue is suitable for use in kitchens, window frames and joints subject to short-term water contact. Water Resistant Wood Glue can be used as an adhesive for wood, veneer, wood blocks, laminate flooring etc. Water Resistant Wood Glue complies with creep test requirements of BS 4071.



For further information, consult our Technical Department.

LarsenBuildingProducts.com

Belfast 028 9077 4000 Birmingham 028 9053 5409 Dublin 01 8348255



TECHNICAL DATA SHEET

PRODUCT INFORMATION

FORM	Liquid Paste
STANDARD COLOURS:	White
FILM APPEARANCE:	Hard, translucent
SPECIFIC GRAVITY:	1,1g/cm ³
DRY MATTER:	45-47%
MFFT:	5°C
FLASH POINT:	No Risk
COVERAGE:	Neat: 6-10m ² / L
NOTE:	Water Resistant Wood Glue is not suitable for use in areas in permanent contact with water.

DIRECTIONS FOR USE

PREPARATION

All surfaces must be sound, clean and free from oil, grease, paint, dust and all other contamination.

APPLICATIONS

Apply neat as an even film to one of the surfaces to be bonded. Form the joint with the adhesive is still tacky. Apply gentle pressure until the adhesive has set. Remove excess adhesive, before it has set, with a damp cloth. Rinse out the applicator nozzle with warm water after use.

IMPORTANT

On extended storage, especially in cold conditions, Water Resistant Wood Glue may thicken. This effect is reversible with slight stirring or shaking. Water Resistant Wood Glue is not suitable for use where permanent contact with water is anticipated. Do not apply below 5°C.

CLEANING

Clean tools, equipment etc. using cold water.

STORAGE

Water Resistant Wood Glue should be stored in closed containers protected from extremes of temperature.

SHELF LIFE

12 months in unopened manufacturer's containers.

PACKAGING

0.25L, 0.5L, 1L, 2.5L and 5L packs.