

DECLARATION OF PERFORMANCE

in accordance with Annex III of the Construction Products Regulation (EU) No 305/2011

No. DOP-12004-001

1. *Unique identification code of the product-type:*

Formulation Ref: FSG008

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

Trade Name: Trade Fast Set (grey)

Batch number: see packaging of the product

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

Fast Setting cementitious adhesive for internal and external tiling

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

Larsen Manufacturing Ltd t/a Larsen Building Products

4 West Bank Road

Harbour Industrial Estate

Belfast

BT3 9JL

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

not relevant

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

System 3

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

The notified body NB1289, performed product type testing on samples taken by Larsen Building Products and issued test report (133155)-13809.

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

not relevant

9. Declared performance

Essential characteristics	Performance	Harmonised Technical specification
Reaction to fire	Class E <small>(as per Commission Decision 2010/81/EU)</small>	EN 12004:2007+A1:2012
Release of Dangerous Substance	See MSDS	
Bond Strength, as:		
- early tensile adhesion strength	$\geq 0.5 \text{N/mm}^2$	
- initial tensile adhesion strength	$\geq 0.5 \text{N/mm}^2$	
Durability, for:		
- tensile adhesion strength after heat ageing	$\geq 0.5 \text{N/mm}^2$	
- tensile adhesion strength after water immersion	$\geq 0.5 \text{N/mm}^2$	
- tensile adhesion strength after freeze thaw cycles	$\geq 0.5 \text{N/mm}^2$	

This cementitious adhesive meets the requirements of EN12004:2007+A1:2012 for **Class C1F**.

10. *The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.*

Signed for and on behalf of the manufacturer by:



.....
Dr Rachel McGlinchey
Product Development Chemist

20/01/2022
Belfast