

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Highways MBC10

Revision 10 **Revision date** 2023-09-20

SECTION 1: Identification of the substance/mixture and	d of the company/undertaking
--	------------------------------

1.1. Product identifier

Produ	ict name	
Other	means of	identification /
UFI		

Highways MBC10

UFI: 6R8C-G3N9-5NKH-96VH.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with
	intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a
	matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;

Description A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.

1.3. Details of the supplier of the safety data sheet

Larsen Building Products Ltd

Address 4 West Bank Road

Belfast Harbour Industrial Estate

Belfast BT3 9JL United Kingdom

www.larsenbuildingproducts.com

+44 (0)28 9077 4000 **Telephone** +44 (0)28 9077 6945 Fax **Email**

I.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number

Emergency	telep	hone	number
-----------	-------	------	--------

(00353) 01 809 2166

Company

Web

National Poisons Centre of Ireland

8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification -	EC
1272/2008	

Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;

2.2. Label elements

Hazard pictograms





Signal Word

Hazard Statement

Danger

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Revision 10 Revision date 2023-09-20

2.2. Label elements

	Eye Dam. 1: H318 - Causes serious eye damage.
Precautionary Statement:	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
Prevention	P264 - Wash thoroughly after handling.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .
Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
	P310 -Immediately call a POISON CENTER/doctor/ .
	P321 - Specific treatment (see on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement:	P501 - Dispose of contents/container to appropriate waste disposal site
Disposal	

Further information

This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Silicon Dioxide		69012-64-2	273-761-1		1 - 10%	
Portland Cement		65997-15-1	266-043-4		20 - 30%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
Calcium Sulphate		7778-18-9	231-900-3		10 - 20%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Revision 10 Revision date 2023-09-20

6.1. Personal precautions, protective equipment and emergency procedures		
	Engure adequate ventilation of the working	

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Calcium Sulphate	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total respirable dust:
Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Silicon Dioxide	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 6 inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:
	WEL 8-hr limit mg/m3 total 0.3 respirable dust:	WEL 15 min limit mg/m3 total respirable dust:
Titanium Dioxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering	Ensure adequate ventilation of the working area.
controls	
8.2.2. Individual protection	Appropriate dedicated workwear is generally sufficient under normal handling conditions.
measures	
Eye / face protection	Suitable eye protection.
Skin protection -	Wear suitable gloves.
Handprotection	

Revision 10 Revision date 2023-09-20

8.2. Exposure controls

Skin protection - Other

After contact with skin, wash immediately with plenty of water.

Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Powder/Granules. Appearance Colour Grev Not applicable. pΗ Initial boiling point Not applicable. Flash point Not applicable. Upper Explosive Limit Not applicable. Lower Explosive Limit Not applicable. Vapour pressure Not applicable. **Relative Vapour Density** Not applicable. Density / Relative Density No data available Partition coefficient Not applicable.

(n-octanol/water)
Autoignition temperature
Decomposition temperature

position temperature Viscosity Solubility Not applicable. Not applicable. Not applicable.

Slightly miscible in water

9.2. Other information

VOC (Volatile organic Not applicable. compounds)

SECTION 10: Stability and reactivity

10.1. Reactivity

Avoid contact with: Strong acids. Avoid contact with: Strong bases.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Organic materials.

10.4. Conditions to avoid

Heat, sparks and open flames.

Further information

Avoid formation of dust.

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin	May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May
sensitisation	produce an allergic reaction.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).

Revision 10 Revision date 2023-09-20

	Trevision date 2020-03-20
11.1 Information on hazard clas	sses
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met).
11.1.4. Toxicological Information	on
	No data available
SECTION 12: Ecological inf	formation
12.1. Toxicity	
	No data available
Further information	
	No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.
SECTION 13: Disposal con	siderations
General information	
	Dispose of in compliance with all local and national regulations. Eurpoean Waste Catalogue:. 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.
Disposal methods	
	Do not empty into drains; dispose of this material and its container in a safe way.
SECTION 14: Transport info	ormation
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es	s)
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	
	The product is not classified as dangerous for carriage.
14.6. Special precautions for us	ser
	The product is not classified as dangerous for carriage.
14.7 Maritime Transport in bulk	according to IMO instruments
	The product is not classified as dangerous for carriage.
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory in	formation

SECTION	16: Other	information

Other information

Revision	This document differs from the previous version in the following areas:.	
	1 - Other means of identification / UFI.	

Revision 10 Revision date 2023-09-20

Other information	
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation.
Further information	·
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.